



EX SERIES

EX5310 ROPS • EX5810 ROPS

53 - 58 HP



1800 186 866
WWW.KIOTI.COM.AU

KIOTI EX SERIES

KIOTI EX SERIES. EXTRA POWER, EXTRA STANDARD FEATURES, EXTRA COMFORT



The measure that makes a tractor a true asset is the boost it gives to your productivity. It has to deliver enough power and versatility for a wide range of applications, day in, day out, season after season. This is where Kioti's EX Series outperforms the competition and offers unbeatable value.

With two engine configurations, 53 hp and turbo-aspirated 58hp, many features give these tractors the edge over the competition, including the powerful hydraulic system flow, 12 x 12 three-range

smooth synchro shuttle transmission, 2 sets standard rear remotes, a generous 3pl lift capacity of 1131 kg, standard loader with 4-in-one bucket and standard three-speed auto PTO.

The flat platform operator area has a no-slip mat, standard foot-activated tilt steering column and fully adjustable deluxe suspension seat for all-day comfort. High ground speed, push button 4WD, and power steering give you confidence, traction and excellent manoeuvrability in changing ground conditions.



MAIN FEATURES

- Powerful 53 hp/58 hp engine
- Synchro shuttle transmission
- 12 x 12 speed transmission
- 62.4 LPM hydraulic pump flow
- 1,131 kg 3 PL capacity @ 610 mm
- Two sets of rear remote outlets
- Auto PTO
- 540 - 750 - 1000 PTO speeds
- Flat working platform
- Tilt steering wheel
- Deluxe suspension seat



Adjustable mechanical suspension seat making operation more comfortable.



Well placed forward/reverse shuttle lever for ease of operation



Convenience of a 3 speed PTO, 540 750 and 1000rpm. A speed for every job.



Electronically engaged 4WD operation.



A rear lift capacity of 1131 kg. Standard with 2 sets of rear hydraulic remotes.



A flat operator station, with a tilt steering column and ergonomically placed controls.

Some images show machinery that is not included in the standard specification sale.

WHETHER YOU COMPARE SPECS AND CRUNCH THE NUMBERS YOURSELF, OR HAVE A CHAT WITH YOUR LOCAL DEALER, THE ULTRA-VERSATILE EX SERIES ADDS UP TO A GREAT CHOICE FOR A BETTER TRACTOR.

SPECIFICATIONS



ISO 9001
NO.204526



ISO 14001
NO.771475



ISO 45001
NO.4033008

MODEL		EX5310	EX5810
ENGINE			
Model		4B243DM-C1	4B243DTM-C
Type		4Cyl, In-line Vertical(Water-cooled, 4-cycle diesel engine)	
Engine Max	HP	53	58
Engine Gross	HP	50	55
Rated revolution	rpm	2,600	
Displacement	cc	2,435	
Fuel Tank	L	45	
DRIVE TRAIN			
Clutch		Dry type single stage	
Transmission		Manual	
Speeds		12	
Differential Lock		Rear Standard	
Brake		Wet Disc Type	
PTO Type		Independent	
Rear PTO (Standard)	rpm	540, 750, 1000	
4WD Type		Electronic Actuation	
HYDRAULIC SYSTEM			
Pump		Gear	
Pump Capacity (Max. Flow Rate)	L/min	62.4	
3-Point Hitch		Category 1	
Maximum Lifting Capacity (600mm aft. of hitch)	kg	1131	
Number of Remote Valves		2	
TIRE SIZE			
Front (AG)		9.5 - 16	
Rear (AG)		13.6 - 26	
TRAVELLING SPEEDS			
Forward	km/h	15-27.9	
Reverse	km/h	14-24.8	
DIMENSIONS			
Overall Length (includes 3-Point Hitch)	mm	3,158	
Overall Width (minimum Tread)	mm	1,675	
Overall Height	mm	2,550	
Wheelbase	mm	1,919.5	
Minimum Ground Clearance	mm	405	
Tread	Front (AG)	mm	1,410
	Rear (AG)	mm	1,324
Minimum Turning Radius (with brake)	mm	3,130	
Weight (with ROPS)	kg	1,790	1,795

STANDARD EQUIPMENT

- 4WD
- Rear PTO
- Joystick Valve
- Horn
- Head Lamp
- Signal Lamp
- Fuel Tank Cap
- PTO Cover

OPTIONAL EQUIPMENT

- Front Weight
- Rear Weight
- Rear View Mirror
- 7 Pin Socket
- Rear Work Light
- Sun Canopy
- Front Grille Guard

*Note: The specifications are subject to change for the purpose of improvement without any notice.